

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 July 2004 (08.07.2004)

PCT

(10) International Publication Number
WO 2004/057186 A1

(51) International Patent Classification: F04B 35/04,
39/02

(21) International Application Number:
PCT/KR2003/001373

(22) International Filing Date: 10 July 2003 (10.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2002-0081900
20 December 2002 (20.12.2002) KR

(71) Applicant (for all designated States except US): LG
ELECTRONICS INC. [KR/KR]; 20, Yoido-Dong,
Youngdungpo-Gu, Seoul 150-010 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KWON, Gi-Bong
[KR/KR]; Daedong Apt. 608-1301, Seokbongmaeul,
Sammoon-Li, Jangyu-Myeon, Gimhae, Gyungsang-
nam-Do 621-831 (KR). JUNG, Won-Hyun [KR/KR];
Seongwon 1st Apt. 106-404, Namyang-Dong, Chang-
won, Gyungsangnam-Do 641-751 (KR). LEE, Su-Won

[KR/KR]; Seongwon 1st Apt. 113-1302, Namyang-Dong,
Changwon, Gyungsangnam-Do 641-751 (KR). LEE,
Dong-Won [KR/KR]; Daedong Apt. 107-1204, Sang-
nam-Dong, Changwon, Gyungsangnam-Do 641-777 (KR).


(74) Agent: PARK, Jang-Won; Jewoo Bldg. 5th Floor, 200,
Nonhyun-Dong, Gangnam-Gu, Seoul 135-010 (KR).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK,
LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX,
MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD,
SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG,
US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: REFRIGERATING SYSTEM HAVING RECIPROCATING COMPRESSOR



(57) Abstract: A refrigerating system includes: an evaporator (2) for performing a cooling operation as a refrigerant is evaporated; a compressor (4) for compressing the refrigerant discharged from the evaporator as a mover is reciprocally moved; a condenser (86) for changing the refrigerant compressed in the reciprocating compressor to a liquid refrigerant; and a capillary tube (8) for decompressing the refrigerant discharged from the condenser and transferring it to the evaporator. Hydrocarbon consisting of carbon and hydrogen, a sort of natural refrigerant, is used as the refrigerant, and a paraffin-based lubricant, a sort of a mineral oil, is used as the lubricant, so that a lubricating performance and a performance of the refrigerating system can be improved.

WO 2004/057186 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

REFRIGERATING SYSTEM HAVING RECIPROCATING COMPRESSOR**TECHNICAL FIELD**

The present invention relates to a refrigerating system for performing a
5 compressing operation on a refrigerant by a reciprocating compressor and,
more particularly, to a refrigerating system having a reciprocating compressor
that is capable of improving a lubrication performance and a performance of a
refrigerating system as well by using a lubricant having an excellent
compatibility with a natural gas for a reciprocating compressor of the
10 refrigerating system which uses the natural gas.

BACKGROUND ART

As chlorofluorocarbon (CFC), a refrigerant used for a refrigerator, an
air-conditioner or the like, has been known as a source material damaging an
15 ozone layer of the stratosphere, researches on a substitute refrigerant is being
actively conducted.

The CFC comprises R11 (trichloromonogluoromethane), R12
(dichlorodifluoromethane), R13 and the like, of which R12 mainly used as a
refrigerant for a refrigerator is one of regulation-subject materials as being a
20 source material causing an ozone layer reduction and generating a global
warming effect. Thus, researches on a natural refrigerant is being actively
conducted as a substitute refrigerant.

The natural refrigerant refers to a material used as a refrigerant which

naturally exists in the globe such as water, ammonia, nitride, carbon dioxide, propane, butane and the like, not an artificial compound. Known that it does not have a bad influence on the global environment, application of the natural refrigerant as a refrigerant is positively reviewed.

5 Among the natural refrigerants, hydrocarbon comprises only carbon and hydrogen and includes methane (R50), ethane (R170), propane (R290), butane (R600), isobutane (R600a), propylene (R1270) or the like. The hydrocarbon is not toxic, chemically stable and especially exhibits an appropriate solubility in a mineral oil.

10 In addition, the hydrocarbon has a zero ozone depletion potential and a very low global warming index. That is, when a global warming index of carbon dioxide is admitted as '1', a global warming index of R12 is 7100, R134a is 1200, while propane is very low, 3.

15 Especially, isobutane (R600a) is an environmental-friendly natural gas which does not damage the ozone layer and have no influence on a greenhouse effect. That is, isobutane (R600a), a sort of a natural gas obtained by refining hydrocarbon gas created in an oil refining process to a high degree of purity, is a refrigerant containing no environmentally detrimental factor.

20 However, with all those advantages, isobutane (R600a) is hardly combined with refrigerant oil currently used for a refrigerating system due to its chemical and electrical properties. Therefore, a refrigerant oil suitable for isobutane (R600a) is in need of development. Especially, necessity of a

refrigerant oil usable for a reciprocating compressor for compressing isobutane (R600a) comes to the front.

Figure 1 illustrates a construction of a refrigerating cycle of a general refrigerating system.

5 As shown in Figure 1, a currently used refrigerating cycle includes: an evaporator 2 for performing a cooling operation as a low temperature and low pressure liquid refrigerant is evaporated; a compressor 4 for compressing the low temperature and low pressure gaseous refrigerant discharged from the evaporator 2 to a high temperature and high pressure gaseous refrigerant; a condenser 6 for
10 changing the high temperature and high pressure gaseous refrigerant discharged from the compressor 4 to a high temperature and high pressure liquid refrigerant; and a capillary tube 8 for decompressing the refrigerant discharged from the condenser 6 so as to be easily evaporated and transferring it to the evaporator 2.

15 The refrigerant used for the refrigerating system is a natural refrigerant, and hydrocarbon is especially used.

Since the lubricant 50 used for the reciprocating compressor of the refrigerating system is used as a refrigerant oil for the compressor compressing a natural refrigerant, its physical and chemical characteristics should be in good
20 harmony with the natural refrigerant.

Namely, the lubricant used as the refrigerant oil of the reciprocating compressor needs to have characteristics that it can protect well an oil film even

though the refrigerant is dissolved, should be thermally and chemically stable so as not to react in spite of being in contact with the refrigerant and an organic material metal at a high temperature or at a low temperature, and should have a high level thermal stability so as not to generate a carbon sludge or not to be oxidized at a high temperature part of the compressor.

In order to satisfy those characteristics, characters of the lubricant, such as a kinematic viscosity, a pour point, a density, a total acid number, a water content or the like, work as critical factors.

Therefore, if the lubricant used for the reciprocating compressor compressing the natural refrigerant is not well harmonized with the refrigerant of the refrigerator, the oil would be leaked. Then, oil circulation is deteriorated to degrade a heat transfer performance of the refrigerator and a lubrication performance, resulting in that frictional portions of each motional part are abraded and thus each part is damaged.

DISCLOSURE OF THE INVENTION

Therefore, it is an object of the present invention to provide a refrigerating system having a reciprocating compressor that is capable of improving a lubrication performance and a performance of a refrigerating system as well by using a natural gas as a refrigerant for the refrigerating system and using a lubricant well harmonized with the natural gas for the reciprocating compressor.

To achieve these objects, there is provided a reciprocating compressor including: an evaporator for performing a cooling operation as a refrigerant is

evaporated; a reciprocating compressor which includes a driving unit having a stator consisting of an outer stator fixed inside a hermetic container, an inner stator disposed with a certain air gap with an inner circumferential surface of the outer stator, and a winding coil wound at one of the outer stator and the inner stator, to which power is applied from an external source, a mover consisting of magnets disposed at regular intervals between the outer stator and the inner stator and linearly and reciprocally moved when power is applied to the winding coil and a magnet frame, in which the magnets are mounted, for transmitting a linear reciprocal motional force to a compression unit, a compression unit for performing a compressing operation on a refrigerant upon receiving the linear reciprocal motional force of the driving unit, and a lubrication unit for supplying the lubricant, a sort of a mineral oil, to each motional portion of the driving unit and the compression unit and performing a lubricating operation; a condenser for changing the refrigerant compressed in the reciprocating compressor to a liquid refrigerant; a capillary tube for decompressing the refrigerant discharged from the condenser and transmitting it to the evaporator; an organic compound refrigerant sucked into the evaporator and comprising carbon and hydrogen, a sort of natural refrigerant, and having combustibility and explosiveness; and a mineral-based lubricant stored inside a hermetic container of the reciprocating compressor and performing a lubricating operation on each sliding part.

In the refrigerating system of the present invention, a controller is additionally provided to vary a capacity of the compressor according to an ambient temperature and environment.

In the refrigerating system of the present invention, the controller determines an output value according to a phase difference between a current and a voltage.

In the refrigerating system of the present invention, the compression unit
5 includes a piston connected to the mover and linearly and reciprocally moved; a cylinder, into which the piston is slidably inserted, forming a certain compression chamber; a suction valve mounted at a refrigerant passage 56 formed at the piston and preventing a backflow of the refrigerant after being introduced into the compression chamber; and a discharge valve mounted at the front side of the
10 cylinder and performing an opening and closing operation on a compressed refrigerant.

In the refrigerating system of the present invention, the lubrication unit includes a lubricant pumping unit for pumping a lubricant filled with a certain amount at a lower portion of the hermetic container; and a lubricant supply
15 passage for supplying the lubricant pumped by the lubricant pumping unit to a frictional portion between the piston and the cylinder.

In the refrigerating system of the present invention, isobutane (R600a) which is hydrocarbon-based and has a molecular formula of $\text{CH}(\text{CH}_3)_3$ is used as the refrigerant.

20 In the refrigerating system of the present invention, the lubricant is a paraffin-based lubricant.

In the refrigerating system of the present invention, the lubricant has a density of $0.866\sim 0.880 \text{ g/cm}^3$ and a flash point of above 140°C .

In the refrigerating system of the present invention, the lubricant has a kinematic viscosity of 7.2~21.8 MM²/s at a temperature of 40°C and a viscosity index of 73~99.

In the refrigerating system of the present invention, the lubricant has a flow
5 point of below -25°C and a total acid number of below 0.01 mgKOH/g.

In the refrigerating system of the present invention, the lubricant has a water content of below 20 ppm and a breakdown voltage of above 30kV.

BRIEF DESCRIPTION OF THE DRAWINGS

10 Figure 1 shows a construction of a refrigerating cycle of a general refrigerating system; and

Figure 2 is a sectional view of a general reciprocating compressor.

MODES FOR CARRYING OUT THE PREFERRED EMBODIMENTS

15 Figure 1 shows a construction of a refrigerating cycle of a general refrigerating system, and Figure 2 is a sectional view of a general reciprocating compressor.

The refrigerating cycle of the refrigerating system includes: an evaporator 2 for performing a cooling operation as a low temperature and low pressure liquid
20 refrigerant is evaporated; a compressor 4 for compressing the low temperature and low pressure gaseous refrigerant discharged from the evaporator 2 to a high temperature and high pressure gaseous refrigerant; a condenser 6 for changing

the high temperature and high pressure gaseous refrigerant discharged from the compressor 4 to a high temperature and high pressure liquid refrigerant; and a capillary tube 8 for decompressing the refrigerant discharged from the condenser 6 so as to be easily evaporated and transferring it to the evaporator.

5 The refrigerating system includes a controller (not shown) which determines an output value according to a phase difference between a current and a voltage in order to vary a capacity of the compressor depending on an ambient temperature and environment.

10 As shown in Figure 2, the compressor 4 includes: a hermetic container 24 to which a suction pipe 20 for sucking a refrigerant and a discharge pipe 22 for discharging a compressed refrigerant; a driving unit 26 disposed inside the hermetic container 24 and generating a reciprocal motional force; a compression unit 28 for performing a compressing operation on the refrigerant upon receiving a reciprocal motional force generated from the driving unit 26; and a lubrication
15 unit 30 for performing a lubrication operation on each motional portion of the driving unit 26 and the compression unit 28.

20 The driving unit 26 consists of a stator 32 fixed inside the hermetic container 24, and a mover 34 disposed spaced apart from the stator 32 and linearly and reciprocally moved by an interaction with the stator 32 when power is applied to the stator 32.

 The stator 32 includes a cylindrical outer stator 38 fixed by a support frame 36 fixed inside the hermetic container 24, an inner stator 40 disposed with a certain air gap with an inner circumferential surface of the outer stator 38, and a

winding coil 42 wound inside the outer stator 38 to which power is applied from an external source.

The mover 34 includes a magnet 46 disposed with a certain space between the outer stator 38 and the inner stator 40 and linearly and reciprocally moved when power is applied to the winding coil 42, and a magnet holder 48 having magnets 46 mounted at equal intervals at its an outer circumferential surface and being connected to a piston 50 of the compression unit 28.

The compression unit 28 includes a piston 50 connected to the magnet holder 48 and linearly and reciprocally moved; a cylinder 54 into which the piston 50 is slidably inserted to form a certain compression chamber 36; a suction valve 58 mounted at a refrigerant passage 56 formed at the piston 50 and preventing a backflow of the refrigerant after being introduced into the compression chamber 52; and a discharge valve 60 mounted at the front side of the cylinder 54 and performing an opening and closing operation on a compressed refrigerant.

The lubrication unit 30 includes a lubricant 62 filled with a certain amount at the lower portion of the hermetic container 24; a lubricant pumping unit 68 for pumping the lubricant 62; and a lubricant supply passage 64 for supplying the lubricant 62 pumped by the lubricant pumping unit 68 to a frictional portion between the piston 50 and the cylinder 54.

The operation of the refrigerating system constructed as described above will now be explained.

When the compressor 4 is driven, the low temperature and low pressure gaseous refrigerant is compressed to a high temperature and high pressure

gaseous refrigerant, which is then introduced into the condenser 6 and changed to a liquid refrigerant. The liquid refrigerant discharged from the condenser is decompressed while passing through the capillary tube 8 and then transferred to the evaporator 2. At this time, air is cooled while passing through the evaporator
5 2 and supplied into the refrigerating system, thereby performing a cooling operation therein.

The operation of the reciprocating compressor will now be described in detail.

When power is applied to the winding coil 42, a flux is formed around the
10 winding coil 42, forming a closed loop along the outer stator 38 and the inner stator 40. By the interaction of the flux formed between the outer stator 38 and the inner stator 40 and the flux formed by the magnet 46, the magnet 46 is linearly moved in an axial direction. When the direction of a current applied to the winding coil 42 is changed in turn, the magnet 46 is linearly and reciprocally moved as the
15 direction of the flux of the winding coil 42 is changed.

Then, the motion of the magnet 46 is transferred to the piston 50 by the magnet holder 48, and accordingly, the piston 50 is linearly and reciprocally moved inside the cylinder 54, thereby performing a compressing operation on the refrigerant.

20 That is, when the piston 50 is retreated, the refrigerant introduced into the suction pipe 20 is supplied to the compression chamber 52 through the suction passage 56 formed at the piston 50. Meanwhile, when the piston 50 advances, the suction passage 56 is closed by the suction valve 58, the refrigerant inside the

compression chamber 52 is compressed, and the compressed refrigerant is externally discharged through the discharge pipe 22

During the compressing operation, the lubricant 62 filled in the hermetic container 24 is pumped according to operation of the lubricant pumping unit 68
5 and supplied to the frictional portion between the piston 50 and the cylinder 54 through the lubricant supply passage 64, for a lubricating operation.

An environment-friendly natural refrigerant is used for the refrigerating system constructed and operated as described above.

Among natural refrigerants, an organic compound refrigerant consisting of
10 only carbon and hydrogen is mainly used, of which hydrocarbon has no toxicity, is chemically stable, has a zero ozone depletion potential and a very low global warming index. The hydrocarbon includes R50 (methane), R170 (methane), R290 (propane), R500 (butane), R600a (isobutane) or R1270 (propylene), etc.

Especially, isobutane (R600a) is a hydrocarbon-based, has a molecular
15 formula of $\text{CH}(\text{CH}_3)_3$, and is an environment-friendly natural gas which does neither damage an ozone layer and nor affect a greenhouse effect. As such, isobutane (R600a) is used as a refrigerant compressing by the reciprocating compressor in the present invention.

As the lubricant 50 for making a lubricating operation for the reciprocating
20 compressor of the present invention, a mineral oil is used which has a favorable compatibility with hydrocarbon and satisfies physical and chemical characteristics.

The mineral oil is divided into a paraffin-based mineral oil and a naphtan-based mineral oil. In the present invention, the paraffin-based mineral lubricant

is used.

It is preferred that the paraffin-based lubricant has a density of 0.866~0.880 g/cm³ at a temperature of 15°C.

A flash point of the paraffin-based lubricant varies depending on a size and
5 a type of the reciprocating compressor. Preferably, it is above 140°C, and it can be below 165°C, below 175°C, below 185°C and below 200°C according to the type of an adopted compressor.

A kinematic viscosity of the paraffin-based lubricant is preferably 7.2~21.8 mm²/s at a temperature of 40°C, and most preferably, it is 8.29 mm²/s and 10.3
10 mm²/s depending on the size and type of an adopted reciprocating compressor.

A viscosity index of the paraffin-based lubricant is preferably 73~99.

A flow point of the paraffin-based lubricant is preferably below -25°C.

A total acid number of the paraffin-based lubricant is below 0.01 mgKOH/g.

The total acid number of the lubricant, representing an amount of an acid
15 component contained in an oil, indicates an amount of potassium hydroxide required for neutralizing an acid component contained in 1g of sample oil by the number of mg.

A water content of the paraffin-based lubricant is preferably below 20 ppm.

A breakdown voltage of the paraffin-based lubricant is preferably above 30
20 kV.

As so far described, the reciprocating system having a reciprocating compressor of the present invention has such an advantage that since it uses

hydrocarbon, the natural refrigerant, and the paraffin-based lubricant, a sort of the mineral oil with an excellent compatibility with hydrocarbon as a lubricant for performing a lubricating operation for the reciprocating compressor. Therefore, a lubricating performance of the reciprocating compressor is improved and a
5 performance of the refrigerating system can be enhanced.

It will be apparent to those skilled in the art that various modifications and variations can be made in the refrigerating system having a reciprocating compressor of the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover modifications
10 and variations of this invention provided they come within the scope of the appended claims and their equivalents.

CLAIMS

1. A reciprocating compressor comprising:

an evaporator for performing a cooling operation as a refrigerant is

5 evaporated;

a reciprocating compressor which includes a driving unit having a stator consisting of an outer stator fixed inside a hermetic container, an inner stator disposed with a certain air gap with an inner circumferential surface of the outer stator, and a winding coil wound at one of the outer stator and the inner stator, to

10 which power is applied from an external source, a mover consisting of magnets disposed at regular intervals between the outer stator and the inner stator and linearly and reciprocally moved when power is applied to the winding coil and a magnet frame, in which the magnets are mounted, for transmitting a linear reciprocal motional force to a compression unit, a compression unit for performing
15 a compressing operation on a refrigerant upon receiving the linear reciprocal motional force of the driving unit, and a lubrication unit for supplying the lubricant, a sort of a mineral oil, to each motional portion of the driving unit and the compression unit and performing a lubricating operation;

a condenser for changing the refrigerant compressed in the reciprocating
20 compressor to a liquid refrigerant;

a capillary tube for decompressing the refrigerant discharged from the condenser and transmitting it to the evaporator;

an organic compound refrigerant sucked into the evaporator and

comprising carbon and hydrogen, a sort of natural refrigerant, and having combustibility and explosiveness; and

a mineral-based lubricant stored inside a hermetic container of the reciprocating compressor and performing a lubricating operation on each sliding

5 part.

2. The refrigerating system of claim 1 further comprising: a controller for varying a capacity of the compressor according to an ambient temperature and environment.

10

3. The refrigerating system of claim 2, wherein the controller determines an output value according to a phase difference between a current and a voltage.

15

4. The refrigerating system of claim 1, wherein the compression unit comprises:

a piston connected to the mover and linearly and reciprocally moved;

a cylinder into which the piston is slidably inserted to form a certain compression chamber;

20

a suction valve mounted at a refrigerant passage 56 formed at the piston and preventing a backflow of the refrigerant after being introduced into the compression chamber; and

a discharge valve mounted at the front side of the cylinder and performing

an opening and closing operation on a compressed refrigerant.

5. The refrigerating system of claim 1, wherein the lubrication unit comprises:

5 a lubricant pumping unit for pumping a lubricant filled with a certain amount at a lower portion of the hermetic container; and

a lubricant supply passage for supplying the lubricant pumped by the lubricant pumping unit to a frictional portion between the piston and the cylinder.

10 6. The refrigerating system of claim 1, wherein isobutane (R600a) which is hydrocarbon-based and has a molecular formula of $\text{CH}(\text{CH}_3)_3$ is used as the refrigerant.

7. The refrigerating system of claim 1, wherein the lubricant is a
15 paraffin-based lubricant.


8. The refrigerating system of claim 1, wherein the lubricant has a density of $0.866\sim 0.880 \text{ g/cm}^3$ and a flash point of above 140°C .


20 9. The refrigerating system of claim 1, wherein the lubricant has a kinematic viscosity of $7.2\sim 21.8 \text{ MM}^2/\text{s}$ at a temperature of 40°C and a viscosity index of $73\sim 99$.

10. The refrigerating system of claim 1, wherein the lubricant has a flow point of below -25°C and a total acid number of below 0.01 mgKOH/g.

5 11. The refrigerating system of claim 1, wherein the lubricant has a water content of below 20 ppm and a breakdown voltage of above 30kV.

1/2
FIG. 1





INTERNATIONAL SEARCH REPORT

International application No.
PCT/KR 03/01373-0

CLASSIFICATION OF SUBJECT MATTER

IPC⁷: F04B 35/04 , F04B 39/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC⁷: F04B, F25B, C09K, C10M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI, EPODOC, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6409484 B1 (Hyun) 25 June 2002 (25.06.02) <i>fig. 1.</i>	1-5
X	JP 2000 309790 A (Sanyo Electric) 7 November 2000 (07.11.00) <i>abstract.</i>	1,6,7
A		8-11

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

„A“ document defining the general state of the art which is not considered to be of particular relevance

„E“ earlier application or patent but published on or after the international filing date

„L“ document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

„O“ document referring to an oral disclosure, use, exhibition or other means

„P“ document published prior to the international filing date but later than the priority date claimed

„T“ later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

„X“ document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

„Y“ document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

„&“ document member of the same patent family

Date of the actual completion of the international search

20 October 2003 (20.10.2003)

Date of mailing of the international search report

20 November 2003 (20.11.2003)

Name and mailing address of the ISA/AT

Austrian Patent Office

Dresdner Straße 87, A-1200 Vienna

Facsimile No. 1/53424/535

Authorized officer

WITTMANN K.

Telephone No. 1/53424/380

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.
PCT/KR 03/01373-0

Patent document cited in search report			Publication date	Patent family member(s)			Publication date
JP	A	20003097 90A2		none			
US	B	6409484	2002-06-25	KR	A	2000043076	2000-07-15
				CN	B	1093914B	2002-11-06
				CN	T	1292067T	2001-04-18
				WO	A	0039461	2000-07-06